



Step 1: Preparing the Vehicle

Installation of your Adventure Graphic must be performed in an air temperature that is no less than +40°F (+5°C). Heating the vehicle's interior will help the adhesion process in cold weather.

Step 2: Preparing the Surface

Clean the surface with soap and water. (Note: do NOT use a petroleum or lotion based cleaner OR household glass cleaner such as Windex) Rinse with water and dry with a clean cloth or towel. If glass has been treated with a product such as Rain-X, use Bon-Ami Cleaning Powder or Soft Scrub to remove the glass treatment. Isopropyl alcohol is highly recommended to remove any remaining contaminants as well as promote adhesion.

Step 3: Positioning and Preparing the Graphic

Using masking tape, secure the graphic in the precise desired position over the glass. Determine the center of the graphic and apply one or more strips of masking tape vertically upon the graphic creating a hinge. Next, cleanly cut away any excess material from the outside edge leaving enough material to overlap the outside edge of glass.



Step 4: Beginning the Application

Release one side of the graphic from the glass while keeping your center hinge intact. Pull the released side of the graphic back over the masking tape hinge. Next, you will separate the release liner from the graphic. To do this, sandwich the outside edge of the graphic between two pieces of masking tape. Carefully separate the two pieces of tape. Repeat this step until the black adhesive side releases from the liner. (Note: Due to the irregular edges of the material, please use care in this step) Pull the release liner away and cut it off as close to your hinge as possible. Make sure the adhesive does not touch the glass until you are prepared to squeegee the graphic down.



Step 5: Applying the First Half of the Graphic

Holding the exposed graphic away from the glass, begin to squeegee the graphic down at the center hinge. Use short overlapping vertical strokes with the squeegee. Allow the squeegee to do the application one stroke at a time. Be sure not to tug or pull on the graphic. Continue working towards the outside edge from the center.



Step 6: Applying the Second Half of the Graphic

Now, remove the center masking tape hinge and any other remaining tape. From the center, remove the remaining release liner, exposing the black adhesive. Squeegee down the second half of the graphic using the same methods as were used on the first half.

Step 7: Finishing Touches

Trim away any excess material from around the outside edge of the glass with an Exacto or Snappy knife. Be careful not to cut the trim or rubber seal. Finally, protect the edges by using a Sealit Pen around the outside of the graphic.



Caring for your Graphic

Sliding Rear Window Cabs - We recommend waiting one full week before sliding the window after installation.

Car Washing - Avoid washing your graphic for one full week following the installation.

Power Washing - At a manual car wash, hold the wash wand no closer than ten (10") inches to the surface of the graphic.

Other Cleaning Tips - Do not use abrasive cleaners on your graphic.

Winter Weather - Avoid using an ice scraper on the graphic. Rear window defrosters will not cause damage to the graphic. Using the rear defroster will shorten the time it takes to dry the glass after being exposed to wet weather.

ADVENTURE GRAPHICS ARE DRY APPLICATION ONLY



Do NOT Apply to the Following: Windshields, Driver Door Window or Passenger Door Window. **Please consult your local laws regarding the application of this material to vehicle glass.**

Condensation Effects: Rain, Snow and Car Washes can all contribute to poor to zero visibility through your Adventure Graphic. Use a towel to dry the surface of the image before driving your vehicle for a clearer view.